



## Coated Fire Hose



Inside Diameter	Mass per Metre	Minimum Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25 mm	0.17 kg	5250 kPa	2100 kPa	0.43 m
38 mm	0.25 kg	5250 kPa	2100 kPa	0.46 m
51 mm	0.34 kg	5250 kPa	2100 kPa	0.49 m
64 mm	0.38 kg	5200 kPa	2100 kPa	0.51 m
65 mm	0.38 kg	5200 kPa	2100 kPa	0.51 m

\* For bigger diameters, refer to Centurion or Rapier.

### Features:

- ✓ Coated fire hose
- ✓ Working Pressure 2100 kPa
- ✓ Mildew resistant
- ✓ No drying after use
- ✓ Available in Red, Green and Yellow
- ✓ 12-month warranty



SPACE SAVING



NO MAINTENANCE



ABRASION RESISTANT



LIGHT WEIGHT



MILDEW RESISTANT



FLEXIBLE

**CAVALIER®** is a fire hose with an extra coating, which improves abrasion resistance and keeps it clean. It is manufactured by weaving a polyester textile reinforcement and coating it for extra protection. The coating comes in a standard red but yellow and green is available as well. This hose is easy to wipe clean after use and does not require drying.

**CAVALIER®** is a high-pressure *Class H* fire hose which is used to protect many commercial and industrial sites. It can also be used for high- pressure wash-down applications. It is easy to roll up after use and it takes up little space in a fire cabinet.

**CAVALIER®** is manufactured in our ISO 9001 quality-accredited factory and can be fitted to a wide range of couplings.

