



Potable Water Transfer



LANCER™ is a potable water transfer hose made exclusively by Crusader Hose. It is designed primarily for municipal use but is also popular in the mining and chemical industries. **LANCER™** is made with a polyester yarn textile reinforcement and encased with thermoplastic polyurethane (PU). This PU-lined hose is also available in an uncoated version.

LANCER™ is suitable for temporary water by-pass when potability is essential. It is also suitable for high-pressure pumping in industrial applications. It is unaffected by UV degradation and is resistant to acids and other chemicals. Its lightweight/low volume coil characteristic makes **LANCER™** easy to handle and store.

LANCER™ is Australian made and manufactured in our ISO 9001 quality-accredited factory. It has Australian Standard AS 4020 approval for drinking water. It also conforms to German BGA DIN39 potability standard. **LANCER™** is backed by a 12-month warranty against manufacturing faults.

Features:

- ✓ Potable water approved AS4020
- ✓ Available as Extruded or Uncoated
- ✓ Working Pressure up to 2100 kPa
- ✓ Light and quick to deploy
- ✓ Low storage space
- ✓ Assembly and fittings available
- ✓ Various colours subject to quantity



Inside Diameter	Mass per Metre	Minimum Burst Pressure	Recommended Working Pressure	Exterior Cover
19 mm	0.13 kg	5250 kPa	2100 kPa	Extruded
25 mm	0.23 kg	5250 kPa	2100 kPa	Extruded
38 mm	0.30 kg	5250 kPa	2100 kPa	Extruded
51 mm	0.43 kg	5250 kPa	2100 kPa	Extruded
65 mm	0.56 kg	5250 kPa	2100 kPa	Extruded
79 mm	0.80 kg	3500 kPa	1400 kPa	Extruded
90 mm	0.83 kg	3500 kPa	1400 kPa	Extruded
102 mm	0.90 kg	2500 kPa	1000 kPa	Extruded
19 mm	0.11 kg	5250 kPa	2100 kPa	Uncoated
25 mm	0.15 kg	5250 kPa	2100 kPa	Uncoated
38 mm	0.22 kg	5250 kPa	2100 kPa	Uncoated
51 mm	0.27 kg	5250 kPa	2100 kPa	Uncoated
65 mm	0.38 kg	5250 kPa	2100 kPa	Uncoated
79 mm	0.46 kg	3500 kPa	1400 kPa	Uncoated
90 mm	0.50 kg	3500 kPa	1400 kPa	Uncoated
102 mm	0.54 kg	2500 kPa	1000 kPa	Uncoated

