

RAPIER

Extruded Fire Hose



Inside Diameter	Mass per Metre	Minimum Burst Pressure	Recommended Working Pressure	30m Coil Diameter
25 mm	0.23 kg	5250 kPa	2100 kPa	0.39 m
38 mm	0.30 kg	5250 kPa	2100 kPa	0.46 m
45 mm	0.36 kg	5250 kPa	2100 kPa	0.47 m
51 mm	0.43 kg	5250 kPa	2100 kPa	0.48 m
64 mm	0.56 kg	5250 kPa	2100 kPa	0.51 m
65 mm	0.56 kg	5250 kPa	2100 kPa	0.51 m
79 mm	0.80 kg	3500 kPa	1400 kPa	0.53 m
90 mm	0.83 kg	3500 kPa	1400 kPa	0.54 m
102 mm	0.90 kg	2500 kPa	1000 kPa	0.55 m

Features:

- ✓ Abrasion resistant
- ✓ High Working Pressure 2100 kPa
- ✓ Easy to clean
- ✓ No drying
- ✓ Other colours available
- ✓ 12-months warranty



PERCOLATING



MILDREW RESISTANT



BURST PRESSURE



FLEXIBLE



LIGHTWEIGHT



NO MAINTENANCE

RAPIER® is an extruded fire hose with a PVC/nitrile outer cover. It is classified as a Type 3 fire hose and is a popular choice for both fire brigades and for industrial plant protection. The extruded cover gives it protection against abrasion damage and makes it easy to wipe free of oils stains and dirt.

The extruded cover comes in a standard red colour but other colours such as yellow or blue can also be supplied. This can help differentiate between fire hose (red) and wash-down hose (blue) on the same industrial site.

RAPIER® requires no drying and is easy to store. It has Australian Standard AS 2792 and Australian Defence Force DEF 5195A approval. We offer a wide range of couplings, which we securely fit to the hose and provide a test certificate if required. This means that you can confidently protect life and property with a fully approved and tested fire hose.

