

SUNNYFLO

Quality Braided Layflat Hose



SUNNYFLO® is a braided layflat budget hose, which is ideal for lighter-duty applications in the industrial, irrigation and mining industries. Its textile reinforcement is made of braided polyester yarns and has a PVC cover and inner lining

SUNNYFLO® BLUE has a working pressure range from 3 – 6 bar.

Inside Diameter (mm)	Inside Diameter (inches)	Maximum Working Pressure (kPa)	Maximum Burst Pressure (kPa)	Maximum Burst Pressure (PSI)	Wall Thickness (mm)	Standard Coil (m)
38mm	1.5"	551	1654	240	1.40	100
50mm	2"	551	1654	240	1.50	100
64mm	2.5"	448	1344	195	1.50	100
76mm	3"	551	1654	240	1.60	100
102mm	4"	482	1448	210	1.70	100
152mm	6"	310	930	135	1.90	100
203mm	8"	275	827	120	2.20	100

Ideal for:

- ✓ Golf course irrigation
- ✓ Open-end discharge
- ✓ Life-style farming

SUNNYFLO® RED, made with thicker braided polyester yarns, is able to sustain higher working pressures of up to 10 bar.

Inside Diameter (mm)	Inside Diameter (inches)	Maximum Working Pressure (kPa)	Maximum Burst Pressure (kPa)	Maximum Burst Pressure (PSI)	Wall Thickness (mm)	Standard Coil (m)
38mm	1.5"	1000	3100	450	2.00	100
50mm	2"	1000	3100	450	2.20	100
64mm	2.5"	1000	3100	450	2.25	100
76mm	3"	1000	3100	450	2.40	100
102mm	4"	1000	3100	450	2.60	100
152mm	6"	1000	3100	450	3.00	100

